


Hydraulic tube

Ø tube	Dimension	Black tube	Max pressure (bar)	Chrom6 free	Max pressure (bar)	Stainless tube (bright annealed)	Max pressure (bar)
6	6 x 1.0	-	-	1902-06x1.0	444	1920-06x1.0	400
8	8 x 1.0	1900-08x1.0	333	1902-08x1.0	333	1920-08x1.0	310
8	8 x 1.5	1900-08x1.5	499	1902-08x1.5	499	-	-
10	10 x 1.0	1900-10x1.0	282	1902-10x1.0	282	1920-10x1.0	253
10	10 x 1.5	1900-10x1.5	423	1902-10x1.5	423	1920-10x1.5	365
10	10 x 2.0	1900-10x2.0	564	-	-	-	-
10	10 x 2.5	1900-10x2.5		-	-	-	-
12	12 x 1.5	1900-12x1.5	353	1902-12x1.5	353	1920-12x1.5	310
12	12 x 2.0	-	-	1902-12x2.0	470	1920-12x2.0	400
12	12 x 2.5	1900-12x2.5		-	-	-	-
14	14 x 2.0	1900-14x2.0	403	-	-	-	-
15	15 x 1.5	1900-15x1.5	282	1902-15x1.5	282	1920-15x1.5	253
15	15 x 2.0	-	-	1902-15x2.0	376	1920-15x2.0	329
16	16 x 1.5	-	-	-	-	1920-16x1.5	238
16	16 x 2.0	1900-16x2.0	353	1902-16x2.0	353	1920-16x2.0	310
16	16 x 2.5	-	-	1902-16x2.5	441	1920-16x2.5	
18	18 x 1.5	1900-18x1.5	235	-	-	1920-18x1.5	214
18	18 x 2.0	1900-18x2.0	313	1902-18x2.0	313	1920-18x2.0	282
18	18 x 2.5	-	-	1902-18x2.5		-	-
							

Hydraulic tube

Ø tube	Dimension	Black tube	Max pressure (bar)	Chrom6 free	Max pressure (bar)	Stainless tube (bright annealed)	Max pressure (bar)
20	20 x 2.0	1900-20x2.0	282	1902-20x2.0	282	1920-20x2.0	253
20	20 x 2.5	-	-	1902-20x2.5	353	-	-
22	22 x 1.5	-	-	1902-22x1.5	192	-	-
22	22 x 2.0	-	-	1902-22x2.0	256	1920-22x2.0	
22	22 x 2.5	-	-	1902-22x2.5	320	-	-
25	25 x 2.5	-	-	1920-25x2.5	282	1920-25x2.5	
25	25 x 3.0	-	-	1902-25x3.0		1920-25x3.0	
28	28 x 1.5	-	-	1902-28x1.5	151	-	-
28	28 x 2.0	-	-	1902-28x2.0	201	1920-28x2.0	
28	28 x 2.5	-	-	1902-28x2.5	252	1920-28x2.5	
							

Black tube - material: E235+N, phosphated.

Chrom6 free - material: E235+N, galvanized 10-12 microns.

Stainless tube - material: 1.4571/TP316 Ti "CFA" (bright annealed)

TAON

Hydraulik Komponenter

TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tool.

TAON Hydraulic Components ApS • +45 24 48 84 80 • info@taon.dk • www.taon.dk

© TAON Hydraulic will always help you find the best solution.