

Hydraulic hose TrAle

SAE 100 R4 Hose - suction/return hose

Composition:

Inner tube: Special NBR rubber resistant to hydraulic oil.

Reinforcement: two textile braids with one steel wire helix.

Cover: Black rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.



Item no.	DN	Ø in	Ø out	Working pressure (bar)	Working pressure (psi)	Burst pressure bar)	Burst pressure (psi)	Vacuum (bar)	Bending radius (mm)	Weight (kg/m)
ML701019	3/4"	19	32	21	305	84	1218	-0,8	127	0,725
ML701025	1"	25,4	37,4	17	247	68	986	-0,8	152	0,847
ML701032	1 1/4"	31,8	45	14	203	56	812	-0,8	203	1,118
ML701038	1 1/2"	38,1	52	10	145	40	580	-0,8	254	1,454
ML701050	2"	50,8	64	7	102	28	406	-0,8	305	1,834
ML701063	2 1/2"	63,5	77	4	58	16	232	-0,8	356	2,310



TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tool.

TAON Hydraulic Components ApS • +45 24 48 84 80 • info@taon.dk • www.taon.dk

© TAON Hydraulic will always help you find the best solution.