


### CHARACTERISTICS FEATURES, on article EM55-24V - ..X066

Power	5,5kW					
Voltage	24V					
Rotational speed	1800 r/min					
Duty time	S2-30min					
Exitation	Series					
Protection	IP 20					
Insulation	F					
Weight	28kg					
Char curve	H171 2402					
Rotation	CWDE					


Motor coating—white galvanized








### **Engine drawing**





## **Performance Testing Report**





## Possible pumps



Туре	Displacement	Flow		Pressure	Max. Speed	Dimension							
		@ 1500 rpm	@ max. rpm	Pnom	n	Α	В	Inlet			Outlet		
	cm <sup>3</sup> /rev	I/min	l/min	bar	rpm	mm	mm	Е	F	d	E	F	d
20A(C)4.5X066	4.5	6.14	14.33	250	3500	40.2	78	30.2	13.1	M6- 6H	30.2	13.1	M6- 6H
20A(C)6.3X066	6.3	8.69	20.29	250	3500	42	81						
20A(C)8.2X066	8.2	11.32	26.4	250	3500	43.5	83.9						
20A(C)10X066	10	13.95	32.55	250	3500	45	87			y			
20A(C)11X066	11	15.76	36.78	250	3500	46	89.1						
20A(C)12X066	12	16.92	39.48	250	3500	46.6	90.3						
20A(C)14X066	14	19.95	46.55	250	3500	48	93.4						1
20A(C)15X066	15	21.6	36	250	2500	49	95	39.7	19	M8- 6H		14.2	
20A(C)16X066	16	23.04	38.4	250	2500	50	96.6						
20A(C)19X066	19	27.36	45.6	200	2500	52	101.5						
20A(C)22X066	22	31.68	42.24	180	2000	55	106.5	4	1				
20A(C)25X066	25	36	48	160	2000	57.2	111.4				39.7	19	M8

